

CR-3200UV4 PLUS CR-3200UV6 PLUS

UV Printer



Four Gen5 Head Speed

CMYK
6pass 720*900dpi 323sqft (30sqm/h)
CMYK + W
6pass 720*900dpi 161sqft (15sqm/h)
CMYK + W + V
6pass 720*900dpi 161sqft (15sqm/h)

Six Gen5 Head Speed

CMYKLCMLM
6pass 720*900dpi 323sqft (30sqm/h)
CMYK + W
6pass 720*900dpi 323sqft (30sqm/h)
CMYK + W + V
6pass 720*900dpi 161sqft (15sqm/h)

SPECIFICATIONS

Model	CR-3200UV PLUS	
Print Head	GEN5 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	128 in.(3250 mm)
	Thickness	Maximum 39 mil(1 mm)
Printing Width	Weight	176 lb.(80 kg)
		126 in.(3200 mm)
Ink Cartridges	Type	UV Curing Ink
	Capacity	Continual Ink Supply System (1.5L ink tank)
Ink Curing Unit	Dual UV LED Lamps	
Printing Resolution	Maximum 1200 dpi	
Interface	USB 2.0	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	216(W)x44(D)x59(H) in. (5480(W)x1120(D)x1500(H) mm)	
Weight(with stand)	4297 lb. (1950 kg)	
Package Dimensions	218(W)x46(D)x74(H) in. (5530(W)x1160(D)x1870(H) mm)	
Package Weight	4408 lb. (2000 kg)	
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, ink cartridges, RIP software, etc.	



- High speed industrial printhead, ensure printing.
- Up to 3200mm width and unlimited length easily.
- With the tension feeding system, ensure every step perfectly works accurately.
- High precision electric negative pressure system.